

## Product data sheet Characteristics

# WHB140-RG

Switch, Weathershield, 1-Gang, 1 Pole, 40A, 250VAC, IP66



#### Main

Range of product	Weathershield
Product brand	Clipsal
Assembly Type	Basic element with complete housing

### Complementary

Number of poles	1
Installation Type	Surface
Local signalling	without
[Ue] rated operational voltage	250 V AC
Rated current	40 A
Marking	ON-OFF
Marking location	Marking on surface
Mounting Type	By screws
Switch function	1-pole

#### **Environment**

- III OI III II II II	
Standards	AS 60529
	AS/NZS 60947-3
	IEC 60669-1
	AS/NZS 3947-3:approval number S/1

### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	7.8 cm	
Package 1 Width	9.2 cm	
Package 1 Length	16.8 cm	
Package 1 Weight	440.0 g	

## Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Toxic heavy metal free	Yes	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Mercury free	Yes
RoHS exemption information	₽
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☐ End Of Life Information

Life Is On