

Product data sheet

Characteristics

RCBE232/30S

Clipsal Resi MAX, RCBO SLIM 1PN 32A C curve 30mA Type A 4500A



Main

Range	Resi MAX
Product or component type	Residual current breaker with overcurrent protection (RCBO)
Product brand	Clipsal
Device application	Distribution
Poles description	1P + N
Neutral position	Left
Number of modules	1
Number of protected poles	1
[In] rated current	32 A
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	C
Earth-leakage sensitivity	30 mA
Earth-leakage protection class	Type A
Breaking capacity	4.5 kA

Complementary

[Ue] rated operational voltage	240 V AC
Control type	ON/OFF locking with trip free mechanism
Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	DIN rail
Size	92.5 x 18 x 71.5 mm conforming to DIN 43880

Environment

Standards	AS/NZS 61009
IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7 cm
Package 1 Width	2 cm
Package 1 Length	9.8 cm
Package 1 Weight	146 g
Unit Type of Package 2	CAR
Number of Units in Package 2	72
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm

Package 2 Weight	10.584 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	864
Package 3 Height	125 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	127.008 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations