Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

II CLIPSAL



ControlLink Remote Switch Mechanism Momentary Push Button, Clipsal Iconic

41EPBM-VW

Main

Range	Clipsal Iconic
Product or component type	Timer
Device presentation	Mechanism

Complementary

Device mounting	Flush	
Actuator	Push-button	
Fixing mode	Clip-in	
Colour tint	Vivid white	
Surface finish	Matt	
Connections - terminals	screw terminals	
Type of packing	Вох	
Sale per indivisible quantity	1	
Remote control type	Wiser room application	
[Ue] rated operational voltage	220240 V AC 50 Hz	
Operating distance	30 m	
Control signal type	ControlLink	
Connections - terminals	Screw terminals	
Number of terminals	2	
Wiring configuration	2-wire	
Material	PC (UL94 V-2): top PC MAS056 (UL94 V-2): bottom	
Height	22 mm	
width	22 mm	
Depth	40 mm	
Embedding depth	38 mm	
Standards	AS/NZS 60669.2.1	

Environment

Ambient air temperature for storage	060 °C
Ambient air temperature for operation	045 °C
Relative humidity	090 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.9 cm
Package 1 Width	6.7 cm
Package 1 Length	8.7 cm
Package 1 Weight	41 g
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Height	9.8 cm
Package 2 Width	13 cm
Package 2 Length	15.6 cm
Package 2 Weight	422 g



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	37
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No