

# Product datasheet

Specifications

**CLIPSAL**



## Switch, Clipsal Iconic Outdoor, Horizontal, 1 Gang, 20A/16AX, 250V

O3041HA-BK

### Main

Range of product	Iconic
Range	Iconic
Product brand	Clipsal
Product or component type	Switch
Assembly Type	Complete product
Device application	Lighting
Outlet standard deviation	Australian
Handle colour	Black
Colour	Black (BK)
Plug, socket category	Low voltage

### Complementary

Number of gangs	1 gang
[Ue] rated operational voltage	230/240 V
Number of poles	1
Mounting position	Horizontal
Installation Type	Surface
Number Of Switches	1
Material	PC (polycarbonate) TPE (thermoplastic elastomer) ABS (acrylonitrile butadiene-styrene) POM (polyoxymethylene)
Installation direction	Horizontal
surface treatment	Untreated
Local signalling	without
[Ue] rated operational voltage	250 V AC 50 Hz
Rated current	20 A at 230/240 V AC 16 AX at 230/240 V AC
Terminals Capacity	4 x 1.5 mm <sup>2</sup> 3 x 2.5 mm <sup>2</sup>
screwdriver shape	Square drive no 1 (SQ1) Philips No 2
Wire stripping length	10 mm
Protection type	Without protection

<b>Marking</b>	Without marking
<b>Mounting Type</b>	By screws By clipping locks
<b>Connections - terminals</b>	Screw terminals 4 x 1.5 mm <sup>2</sup> 2 x 2.5 mm <sup>2</sup>
<b>Surface finish</b>	Matt
<b>Targeted country</b>	Australia
<b>Height</b>	85 mm
<b>Width</b>	115.5 mm
<b>Depth</b>	70 mm
<b>Product weight</b>	0.19 kg
<b>Actuator</b>	Rocker
<b>Mounting support</b>	Wall
<b>Switch function</b>	1-pole 1/2-way

## Environment

<b>Ambient air temperature for operation</b>	0...45 °C
<b>IP degree of protection</b>	IP56
<b>Ambient air temperature for storage</b>	0...60 °C
<b>relative humidity</b>	10...95 %
<b>Electrical durability</b>	12000 cycles
<b>Standards</b>	AS/NZS 3133

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	8.7 cm
<b>Package 1 Width</b>	11.9 cm
<b>Package 1 Length</b>	8.9 cm
<b>Package 1 Weight</b>	222.0 g
<b>Unit Type of Package 2</b>	BB2
<b>Number of Units in Package 2</b>	30
<b>Package 2 Height</b>	30.9 cm
<b>Package 2 Width</b>	41.3 cm
<b>Package 2 Length</b>	45.9 cm
<b>Package 2 Weight</b>	7.66 kg
<b>Unit Type of Package 3</b>	P06
<b>Number of Units in Package 3</b>	360
<b>Package 3 Height</b>	105.0 cm
<b>Package 3 Width</b>	60.0 cm
<b>Package 3 Length</b>	80.0 cm
<b>Package 3 Weight</b>	100.42 kg

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

EU RoHS Directive

Compliant with Exemptions

REACH Regulation

[REACH Declaration](#)

China RoHS Regulation

[China RoHS declaration](#)

## Use Again

### Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Halogen content performance

Halogen free plastic parts product

Take-back

No