

Product datasheet

Specifications

CLIPSAL



Switch, Clipsal Iconic Outdoor, Horizontal, 1 Gang, 20A/16AX, 250V

O3041HA-XW

Main

Range of product	Iconic
Range	Iconic
Product brand	Clipsal
Product or component type	Switch
Assembly Type	Complete product
Device application	Lighting
Outlet standard deviation	Australian
Colour	White (XW)
Plug, socket category	Low voltage

Complementary

Number of gangs	1 gang
[Ue] rated operational voltage	230/240 V
Number of poles	1
Mounting position	Horizontal
Installation Type	Surface
Number Of Switches	1
Material	PC (polycarbonate) TPE (thermoplastic elastomer) ABS (acrylonitrile butadiene-styrene) POM (polyoxymethylene)
Installation direction	Horizontal
surface treatment	Untreated
Local signalling	without
[Ue] rated operational voltage	250 V AC 50 Hz
Rated current	20 A at 230/240 V AC 16 AX at 230/240 V AC
Terminals Capacity	4 x 1.5 mm ² 3 x 2.5 mm ²
screwdriver shape	Square drive no 1 (SQ1) Philips No 2
Wire stripping length	10 mm
Protection type	Without protection
Marking	Without marking

Mounting Type	By screws By clipping locks
Connections - terminals	Screw terminals 4 x 1.5 mm ² 2 x 2.5 mm ²
Surface finish	Matt
Targeted country	Australia
Height	85 mm
Width	115.5 mm
Depth	70 mm
Product weight	0.19 kg
Actuator	Rocker
Mounting support	Wall
Switch function	1-pole 1/2-way

Environment

Ambient air temperature for operation	0...45 °C
IP degree of protection	IP56
Ambient air temperature for storage	0...60 °C
relative humidity	10...95 %
Electrical durability	12000 cycles
Standards	AS/NZS 3133

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.7 cm
Package 1 Width	11.9 cm
Package 1 Length	8.9 cm
Package 1 Weight	274.0 g
Unit Type of Package 2	BB2
Number of Units in Package 2	30
Package 2 Height	30.9 cm
Package 2 Width	41.3 cm
Package 2 Length	45.9 cm
Package 2 Weight	9.22 kg
Unit Type of Package 3	P06
Number of Units in Package 3	360
Package 3 Height	105.0 cm
Package 3 Width	60.0 cm
Package 3 Length	80.0 cm
Package 3 Weight	119.14 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 6

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic Yes

EU RoHS Directive Compliant with Exemptions

REACH Regulation [REACH Declaration](#)

China RoHS Regulation [China RoHS declaration](#)

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Halogen content performance Halogen free plastic parts product

Take-back No