


Product datasheet

Specifications

CLIPSAL



LED Mechanism, Pro Series, 40M,
250V

40N-GR

Main

Range of product	Pro Series
Product or component type	Indicator module
Device presentation	Mechanism with central plate
Type of packing	Polybag

Complementary

Device mounting	Clip with locking bar
[Ue] rated operational voltage	250 V
Surface treatment	Untreated
Local signalling	LED green for status
Material	PC (polycarbonate): housing PA66: housing
Height	23 mm
width	23 mm
Depth	32 mm
Net weight	0.016 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.2 cm
Package 1 Width	2.2 cm
Package 1 Length	2.4 cm
Package 1 Weight	16.98 g

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
--	------------

Packaging without single use plastic	No
--------------------------------------	-----------

Use Again

Repack and remanufacture

Take-back	No
-----------	-----------

Image of product / Alternate images

Alternative

