

# Product datasheet

Specifications



## Clipsal MAX9, Miniature Circuit-Breaker (MCB), 1P, 32A, C Curve, 6000A, 240/415V, Distribution

MX9MC132

### Main

Range	MAX9
Product Or Component Type	Miniature circuit-breaker
Device Application	Distribution
Poles Description	1P
Number Of Protected Poles	1
[In] Rated Current	32 A at 30 °C
Network Type	AC
Network Frequency	50/60 Hz
[Ue] Rated Operational Voltage	240 V AC 50/60 Hz
Curve Code	C
Magnetic Tripping Limit	5...10 x In
Colour	White (RAL 9003)

### Complementary

Breaking Capacity	6000 A Icn at 240 V AC 50/60 Hz conforming to AS/NZS 60898
[Ics] Rated Service Breaking Capacity	6000 A 100 % - 240 V AC 50/60 Hz
Limitation Class	3
[Uimp] Rated Impulse Withstand Voltage	4 kV
[Ui] Rated Insulation Voltage	500 V
Suitability For Isolation	Yes
Contact Position Indicator	Yes
Control Type	Toggle
Local Signalling	ON/OFF indication
9 Mm Pitches	2
Height	85 mm
Width	18 mm
Embedding Depth	44 mm
Depth	75 mm
Net Weight	125 g
Mechanical Durability	20000 cycles
Electrical Durability	10000 cycles 240 V

Heat Dissipation	2.8 W
Provision For Padlocking	Padlockable
Connections - Terminals	Tunnel type terminals (top or bottom) 1...25 mm <sup>2</sup> flexible Tunnel type terminals (top or bottom) 1...35 mm <sup>2</sup> rigid
Wire Stripping Length	14 mm for top or bottom connection
Tightening Torque	3.5 N.m
Grid Distance	45 mm

## Environment

Quality Labels	RCM
Ip Degree Of Protection	IP20
Pollution Degree	2
Overvoltage Category	III
Tropicalisation	Severity B conforming to IEC 60068-2-30
Relative Humidity	95 % at 55 °C
Operating Altitude	0...2000 m
Ambient Air Temperature For Operation	-25...70 °C
Ambient Air Temperature For Storage	-40...85 °C
Temperature Derating Table	-25 °C ( 37.9 A ) -20 °C ( 37.4 A ) -15 °C ( 36.9 A ) -10 °C ( 36.4 A ) -5 °C ( 35.9 A ) 0 °C ( 35.3 A ) 5 °C ( 34.8 A ) 10 °C ( 34.3 A ) 15 °C ( 33.7 A ) 20 °C ( 33.2 A ) 25 °C ( 32.6 A ) 30 °C ( 32 A ) 35 °C ( 31.4 A ) 40 °C ( 30.8 A ) 45 °C ( 30.2 A ) 50 °C ( 29.6 A ) 55 °C ( 28.9 A ) 60 °C ( 28.3 A ) 65 °C ( 27.6 A ) 70 °C ( 26.9 A )

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.2 cm
Package 1 Width	8.5 cm
Package 1 Length	1.8 cm
Package 1 Weight	117.0 g

## Contractual warranty

Warranty	7-year
----------	--------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

RoHS Exemption Information [Yes](#)

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu RoHS Directive Compliant with Exemptions

China RoHS Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations