

Product datasheet

Specifications



Clipsal MAX9, Miniature Circuit-Breaker (MCB), 3P, 32A, C Curve, 6000A, 415V, Distribution

MX9MC332

Main

Range	MAX9
Product Or Component Type	Miniature circuit-breaker
Device Application	Distribution
Poles Description	3P
Number Of Protected Poles	3
[In] Rated Current	32 A at 30 °C 32.0 A at 30 °C
Network Type	AC
Network Frequency	50/60 Hz
[Ue] Rated Operational Voltage	415 V AC 50/60 Hz
Curve Code	C
Magnetic Tripping Limit	5...10 x In
Colour	White (RAL 9003)

Complementary

Breaking Capacity	6000 A Icn at 415 V AC 50/60 Hz conforming to AS/NZS 60898
[Ics] Rated Service Breaking Capacity	6000 A 100 % - 415 V AC 50/60 Hz
Limitation Class	3
[Uimp] Rated Impulse Withstand Voltage	4 kV
[Ui] Rated Insulation Voltage	500 V
Suitability For Isolation	Yes
Contact Position Indicator	Yes
Control Type	Toggle
Local Signalling	ON/OFF indication
9 Mm Pitches	6
Height	85 mm
Width	54 mm
Embedding Depth	44 mm
Depth	75 mm
Net Weight	375 g
Mechanical Durability	20000 cycles

Electrical Durability	10000 cycles 240 V
Heat Dissipation	2.8 W
Provision For Padlocking	Padlockable
Connections - Terminals	Tunnel type terminals (top or bottom) 1...25 mm ² flexible Tunnel type terminals (top or bottom) 1...35 mm ² rigid
Wire Stripping Length	14 mm for top or bottom connection
Tightening Torque	3.5 N.m
Grid Distance	45 mm

Environment

Quality Labels	RCM
Ip Degree Of Protection	IP20
Pollution Degree	2
Overvoltage Category	III
Tropicalisation	Severity B conforming to IEC 60068-2-30
Relative Humidity	95 % at 55 °C
Operating Altitude	0...2000 m
Ambient Air Temperature For Operation	-25...70 °C
Ambient Air Temperature For Storage	-40...85 °C
Temperature Derating Table	-25 °C (37.9 A) -20 °C (37.4 A) -15 °C (36.9 A) -10 °C (36.4 A) -5 °C (35.9 A) 0 °C (35.3 A) 5 °C (34.8 A) 10 °C (34.3 A) 15 °C (33.7 A) 20 °C (33.2 A) 25 °C (32.6 A) 30 °C (32 A) 35 °C (31.4 A) 40 °C (30.8 A) 45 °C (30.2 A) 50 °C (29.6 A) 55 °C (28.9 A) 60 °C (28.3 A) 65 °C (27.6 A) 70 °C (26.9 A)

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.4 cm
Package 1 Width	8.5 cm
Package 1 Length	5.3 cm
Package 1 Weight	356.0 g

Contractual warranty

Warranty	7-year
-----------------	--------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations