

Product datasheet

Specifications

CLIPSAL

Green Premium™



Clipsal MAX9, Residual Current Breaker with Overcurrent Protection (RCBO), 3PN, 10A, 30mA, C Curve, 6000A, A Type, 5 MOD

MX9R3510

Main

Range	MAX9
Product Or Component Type	Residual current breaker with overcurrent protection (RCBO)
Poles Description	3P + N
Number Of Protected Poles	3
[In] Rated Current	10 A at 30 °C conforming to AS/NZS 61009.1
Network Type	AC
Network Frequency	50 Hz
[Ue] Rated Operational Voltage	415 V AC 50 Hz
Curve Code	C
Earth-Leakage Sensitivity	30 mA
Earth-Leakage Protection Class	Type A

Complementary

Earth-Leakage Protection Time Delay	Instantaneous
Breaking Capacity	6000 A Icn at 415 V AC 50 Hz
Limitation Class	3
[Ui] Rated Insulation Voltage	440 V AC 50 Hz
[Uimp] Rated Impulse Withstand Voltage	4 kV
9 Mm Pitches	10
Height	95 mm
Width	90 mm
Depth	75 mm
Net Weight	500 g
Connections - Terminals	Tunnel type terminal - 1...16 mm ² - rigid Tunnel type terminal - 1...10 mm ² - flexible
Comb Busbar And Distribution Block Compatibility	YES

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Temperature Derating Table	-25 °C (12.1 A)
	-20 °C (12.1 A)
	-15 °C (11.8 A)
	-10 °C (11.6 A)
	-5 °C (11.4 A)
	0 °C (11.2 A)
	5 °C (11.02 A)
	10 °C (10.8 A)
	15 °C (10.6 A)
	20 °C (10.4 A)
	25 °C (10.2 A)
	30 °C (10 A)
	35 °C (9.8 A)
	40 °C (9.6 A)
	45 °C (9.3 A)
	50 °C (9.1 A)
	55 °C (8.9 A)
60 °C (8.6 A)	
65 °C (8.4 A)	
70 °C (8.1 A)	

Grid Distance	45 mm
----------------------	-------

Environment

Standards	IEC 61009-2-1 EN/IEC 61009-1 AS/NZS 61009.1
------------------	---

Quality Labels	RCM
-----------------------	-----

Ip Degree Of Protection	IP20
--------------------------------	------

Pollution Degree	2
-------------------------	---

Overvoltage Category	III
-----------------------------	-----

Ambient Air Temperature For Operation	-25...70 °C
--	-------------

Packing Units

Unit Type Of Package 1	PCE
-------------------------------	-----

Number Of Units In Package 1	1
-------------------------------------	---

Package 1 Height	7.8 cm
-------------------------	--------

Package 1 Width	9.1 cm
------------------------	--------

Package 1 Length	9.0 cm
-------------------------	--------

Package 1 Weight	498.0 g
-------------------------	---------

Unit Type Of Package 2	S03
-------------------------------	-----

Number Of Units In Package 2	16
-------------------------------------	----

Package 2 Height	30.0 cm
-------------------------	---------

Package 2 Width	30.0 cm
------------------------	---------

Package 2 Length	40.0 cm
-------------------------	---------

Package 2 Weight	8.409 kg
-------------------------	----------

Contractual warranty

Warranty	7-year
-----------------	--------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations