# **PSA LifeSaver**

# LIFPE10LP


Low Profile 10 Year Sealed Battery



#### **Features**

- Award-winning low profile design
- Measures at 115mm x 23mm
- Surface mount installation
- Powered by 10 year lithium battery (non-replaceable)
- Photoelectric sensing technology
- Easy power on / power off mounting bracket
- Bug screen sensor chamber protection
- · Large and simple to use Test & Hush button
- Hush mode to desensitise the alarm for 10 min
- Loud 85dBA alarm at 3 metres
- Tamper resistant feature
- LED status indicator
- 5 year warranty
- Complies to the Australian Standard AS3786:2014.

### **Dimensions**









## **Specifications**

•		
Model	PE10LP	
Part Number	LIFPE10LP	
Sensor Type	Photoelectric	
Smoke Alarm Power	10 year 3VDC CR123A []xed battery (non-replaceable)	
Alarm Volume	85dBA at 3 metres	
Alarm Signal Pattern	ISO8201 (BI 0.5s -pause 0.5s -BI 0.5s -pause 0.5s -BI 0.5s -pause 1.5s, with the RED LED flashing, repeat this alarm pattern)	
Temperature Range	0°C - 40°C	
Humidity Range	Up to 93% RH (non-condensing)	
Hush Function	Silences alarm for 5 to 15 minutes The red LED flashes every 8 seconds Dense smoke will override hush function	
Alarm Duration	Alarm will sound for as long as smoke is detected, then unit will automatically reset when smoke clears.	
Alarm Indication	Red LED flashes every second.	
Indicator LEDs	Red LED - Alarm status indicator, differentiated by frequency of flashes.	
Low Battery	Red LED flash once every 40 seconds.	
Chamber fault	Red LED flash once every 40 seconds	
Buzzer fault	Red LED flash twice every 40 seconds.	
Approvals	AS3786:2014	
Warranty	5 years	

\*Refer to Installation and User Manual for further information and programming.

Item Code	Single	Pack	Carton
Quantity	1	200	60
Barcode	9318475001868	19318475001865	29318475001862

LIFPE10LP Datasheet V2.00, Document 014. Published 16/07/2024 - Specifications may change without notice.



