

Product data sheet

Characteristics

NEXE302-B

1 G 2 way switch 10A



Main

| | |
|-----------------------|-------------------------|
| Range of product | NEXE |
| Device short name | NEXE302-B |
| Plug, socket category | Low voltage |
| Poles description | L+N |
| Network type | AC |
| Outlet standard | Australian/ New Zealand |

Complementary

| | |
|-------------------------------------|-----------------------|
| Plug, socket, control station shape | |
| Pin number | |
| Shape of pin | |
| Rated current | 10A |
| Rated operational voltage | 250V |
| Network frequency | 50 Hz |
| Material | Polycarbonate ,copper |
| Connections -terminals | Screw terminals |
| Cable entry | |
| Colour | black |

Environment

| | |
|---------------------------------------|----------------------------------|
| Standards | AS 3133:2020 AS/NZS 3100:2022 |
| IP degree of protection | |
| Ambient air temperature for operation | -25...75°C |
| Ambient air temperature for storage | -25...75°C |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | |
| Number of Units in Package 1 | 10 |
| Package 1 Height | 18cm |
| Package 1 Width | 13cm |
| Package 1 Length | 16cm |
| Package 1 Weight | 0.823kg |
| Unit Type of Package 2 | |
| Number of Units in Package 2 | 100 |
| Package 2 Height | 67cm |
| Package 2 Width | 37cm |
| Package 2 Length | 17.5cm |
| Package 2 Weight | 9.23kg |