

MOD6320

NHP MOD6 Miniature Circuit Breaker 6kA 3Pole 20A C Curve



MOD6
MINIATURE CIRCUIT BREAKERS



Component type	Miniature circuit breaker (MCB)
Range	MOD6 MCB
Model	N/A
Product status	Existing

NHP's MOD6 range of miniature circuit breakers offers cost effective solutions while providing core electrical protection, designed to detect and trip on overload and short circuit currents. These MCBs are available with a 6kA short circuit rating, with current ratings from 6-63A in 1P, 2P or 3P in C trip curve.

ELECTRICAL

Rated current	20.0 A
Number of poles (total)	3.0
Trip curve	C
Rated voltage	415.0 V
Frequency	50 - 60 Hz
Voltage type	AC/DC
Rated short-circuit breaking capacity I _{cn} according to AS/NZS 60898 at 230 VAC	6.0 kA
Rated short-circuit breaking capacity I _{cn} according to AS/NZS 60898 at 400 VAC	6.0 kA
Max. rated operation voltage U _e	440.0 V
Rated insulation voltage U _i	440.0 V
Rated impulse withstand voltage U _{imp}	6.0 kV

CONSTRUCTION

Number of protected poles	3.0
Degree of protection (IP)	IP40

MECHANICAL

Connectable conductor cross section solid-core	1 - 25 mm ²
Connectable conductor cross section multi-wired	1 - 25 mm ²

DIMENSIONS

Height	86.0 mm
Width	54.0 mm
Width in number of modular spacings	3.0
Depth	76.0 mm
Weight	0.36 kg

ENVIRONMENT

Pollution degree	3.0
Rated surrounding temperature without derating	30.0 °C
Ambient temperature during operating	-25 - 55 °C

MOD6320

NHP MOD6 Miniature Circuit Breaker 6kA 3Pole 20A C Curve



MOD6
MINIATURE CIRCUIT BREAKERS

DIMENSIONAL DIAGRAM

