

Product Datasheet

Standard Meter Boxes



- IP23 Enclosure
- 1.2mm Galvanised sheet steel or stainless steel
- 12 Pole load centre attachment included
- Internal hinged pre-drilled switch panel, tested for water absorption, insulation resistance & 960°C glow wire by TÜV
- Padlockable vertical door
- Louver ventilation
- Top and bottom cable entry knockouts
- Internal earth stud included

Specifications

Category	Meter Panels
SubCategory	Standard Meter Boxes
IP Rating	IP23
Mounting	Wall Mounted
Provision for Locking	≤ 12mm Hole for Padlock
Cable Entry	Top and bottom (mountable cable holder accessory sold separately)
Body / Housing	Galvanised with bakelite panel, stainless steel option available
Switch Panel	Pre-drilled (SMB900 - Blank).
Space Behind Panel	90mm (175mm for SMB600L.330)
Space in Front of Panel	160 (155 for SMB600L.330)
Load Centre	12 Pole attachment included (SMB900 excluded)
Hinges	Top opening lid, side hinged switch panel
Compliance	NSW Service Installation Rules AS/NZS 61439.1:2016

Product Datasheet

Standard Meter Boxes

Part No.	Description (Dimensions (mm): Height x Width x Depth)
SMB600L	GALVANISED, 600H x 600W x 250D, PRE-DRILLED SWITCH PANEL
SMB600L.330	GALVANISED, 600H x 600W x 330D, PRE-DRILLED SWITCH PANEL
SMB600L.SS	STAINLESS STEEL, 600H x 600W x 250D, PRE-DRILLED SWITCH PANEL
SMB900	GALVANISED, 900H x 900W x 250D, BLANK SWITCH PANEL, LOAD CENTRE EXCLUDED

(SMB600L)

